

Threat Management Gateway Appliance

Integrated Business Security Platform

The nTMG-1500S is a high performance, next generation “all-in-one” integrated business gateway security appliance. It provides applicationlayer Firewalling, IPS, VPN, application publishing, URL Filtering, AntiVirus / Anti-Malware and Email protection for business of all sizes



- Custom-built for Small Sized Business
- Supports up to 500 Connected PCs
- Redundant Hotswap Disks
- Large Network Port Density & Remote KVM Support

nTMG-1500S Integrated Business Security Gateway Features

High Availability Array and Array Management

HA Support	None, Single Server Standalone Configuration
Array Management	<ul style="list-style-type: none"> • Single Server – nTMG only support standalone mode • Regional branches office policy management: Multiple nTMG series appliances policy management through manual import/export of policy templates • Enterprise-Wide EMS Managed Array: Requires purchase of at least one of the nTMGE series appliance for centralized automated policy management via TMG Configuration Storage Server (CSS) in ADAM mode

nAppliance Hardware System Platform Features

Processor	64-bit Single Processor, Dual Core x86 processor architecture. High-speed processor, cache, larger memory and multi lane PCIe bandwidth designs for maximized deep packet content inspection acceleration with lowest packet latency, highest system throughput and unflinching scalability to support large number of processor intensive integrated security applications workload.
Network Ports	6 GbE LANs – High network port density provides the performance and operational flexibility and redundancy required to secure a high-availability network infrastructure, along with economies of scale needed by large companies, enterprise, data centers, and service providers.
Lights-Out Port	Remote Lights-Out-Management (LOM) via dedicated iKVM network Port guarantees uninterrupted Out-Of-Band remote access even when appliance is off.
High System Reliability	<p>Maximum uptime through superior thermal design, component-level redundancy, serviceability and built-in remote lights-out appliance management system:</p> <ul style="list-style-type: none"> • Disk Redundancy: Dual enterprise grade SATA disks and hardware RAID controller for disk mirroring configuration allows uninterrupted system operations in case of a single disk failure. Redundant hot-swap disks offers high availability and no downtime while RAID array is being rebuild on replacement drive. • Power Supply Redundancy: Single, high efficiency power-supply module • System Image Redundancy and Quick Recovery Option: Efficient In-Field Appliance Image Management: Multiple system image partitions. ARRMS provides PiT image recovery backup/restore, factory reset and bare-metal image recovery

nAppliance Oneface™ Management System Features

Embedded Recovery Manager	<p>Appliance Recovery and Remote Management System (ARRMSTM) provides offline and online remote system management and maintenance to the appliance hardware and software image.</p> <ul style="list-style-type: none"> • ARRMS operating environment functions completely independently of the main appliance hardware and software environment. The appliance can boot into “maintenance mode” where the administrator has full BIOS-level access to the hardware and software environments, even with the appliance operating system shutdown or the hardware powered off. • System image backup, restore and “Bare-Metal” recovery. Backup any number of system image to local disk partition, removable media or a network target, such images than can be used for a quick restore to “last good known state”. • Factory-default rest and Bare-Metal appliance recovery support
Embedded Web LOM Manager	Remote Lights-Out-Management (LOM) via dedicated iKVM (Keyboard, Video Mouse port access over Web) network Port guarantees uninterrupted Out-Of-Band remote access and manageability for a complete “As if you were sitting in front of it” experience.
Integrated Oneface™ System Manager	Provides rich and robust set of feature including Backup Manager, security manager, update manager, configuration manager, SNMP agents, alert notification system and a component manager for 3rd party add-on integration

Performance Specifications

Storage Capacity	: 500GB
Deployment Type (Business)	: Small Size
Recommended Corporate PCs	: 500
Recommended Corporate Web Users	: 2,500
Firewall Throughput (Mbps)	: 2,000
HTTP Throughput (Mbps)	: 150
VPN Throughput (Mbps)	: 160

Hardware Specifications

Processor	Single Processor, Dual Core
Memory	4 GB
Network Interfaces (RJ45)	6x GbE LAN
System Management Interface (RJ45)	1x iKVM Lights-Out (IPMI) Remote Access
Storage – Data (Redundant)	Dual SATA Disk, Mirroring (RAID-1)
Storage - Recovery OS (ARRMS)	2 GB, USB Flash DOM
SSL HW Accelerator	---
LCD w/Keypad Display	---
System IO Ports (VGA/USB/Serial)	1 / 2 / 1
AC Power Supply	<ul style="list-style-type: none"> • Single Redundant, 260 Watts • 100 to 240 VAC Auto • 47 to 63 Hz, 3A
Physical Dimensions	<ul style="list-style-type: none"> • Chassis: 19”, 2-post • Height: 1.5” (1U), 1 rack unit; • Width: 17.5”; Depth: 14” • Weight: 30 lbs.
Storage Temperature	-40°F to 122°F (-40°C to 50°C) 5% to 95% relative humidity, non-condensing
Operating Temperature	35°F to 95°F (1.7°C to 35°C) 5% to 95% relative humidity, non-condensing
Agency Certifications	Safety: UL, FCC, CE, TUV, CB Environmental: WEEE and RoHS
Support and Services	Standard warranty includes 30-day software support with one-year hardware support; upgradable

nAppliance delivers Integrated Appliance “Turnkey” Solutions:

nAppliance Networks, an ISO 9001:2000 is a provider of mission critical network edge security infrastructure provider. Unlike alternatives that are simply based on general-purpose server hardware, our appliances are designed for highest reliability, optimized for maximum performance, and manufactured to exact quality specifications. Trust nAppliance Net-Gateway Forefront appliance series to deliver reliable and comprehensive solutions.