

Threat Management Gateway Appliance

Integrated Enterprise Security Platform

The nTMGB-5500B is a high performance, next generation “all-in-one” integrated branch-office gateway security appliance. It helps securely expand corporate networks via secure site-site connectivity, easy deployment, comprehensive manageability and content acceleration.



- Custom-built for Large Sized Branch-Office
- Supports up to 4,000 Connected PCs
- Redundant Hotswap Disks and Power Supply Modules
- Built-in Dual Node High Availability NLB Support
- Powered by Forefront TMG 2010 – Branch-Office Edition

nTMGB-5500B Integrated Enterprise-Wide Branch-Office Security Gateway Features

Scalability, High Availability Array and Array Management

High Availability Support	Up to two Forefront nTMGB appliances can be grouped into a load balancing redundant active/active array using integrated Forefront NLB functionality for redundancy, and increased throughput and user capacity
Array Management	<ul style="list-style-type: none"> • Centralized support via nTMGB series Enterprise gateway appliance located at corporate-headquarter. • Enterprise-Wide EMS Managed Array support, Single nTMGB series appliance manager can manage over 1000 Forefront nTMGB appliances

nAppliance Hardware System Platform Features

Processor	64-bit Dual Processor, Eight Core Xeon x86 processor architecture. High-speed processor, cache, larger memory and multi lane PCIe bandwidth designs for maximized deep packet content inspection acceleration with lowest packet latency, highest system throughput and unflinching scalability to support large number of processor intensive integrated security applications workload.
Network Ports	8 GbE LANs – High network port density provides the performance and operational flexibility and redundancy required to secure a high-availability network infrastructure, along with economies of scale needed by large companies, enterprise, data centers, and service providers.
Lights-Out Port	Remote Lights-Out-Management (LOM) via dedicated iKVM network Port guarantees uninterrupted Out-Of-Band remote access even when appliance is off.
SSL Accelerator	Embedded high performance Cavium SSL Co-processor hardware for 100% TCP/IP Offload for enhanced system stability and performance at peak loads.
High System Reliability	<p>Maximum uptime through superior thermal design, component-level redundancy, serviceability and built-in remote lights-out appliance management system:</p> <ul style="list-style-type: none"> • Disk Redundancy: Dual enterprise grade SATA disks and hardware RAID controller for disk mirroring configuration allows uninterrupted system operations in case of a single disk failure. Redundant hot-swap disks offers high availability and no downtime while RAID array is being rebuild on replacement drive. • Power Supply Redundancy: Dual hot-swap, high efficiency power supply modules. • System Image Redundancy and Quick Recovery Option: Efficient In-Field Appliance Image Management: Multiple system image partitions. ARRMS provides PIT image recovery backup/restore, factory reset and bare-metal image recovery

nAppliance Oneface™ Management System Features

Embedded Recovery Manager	<p>Appliance Recovery and Remote Management System (ARRMSTM) provides offline and online remote system management and maintenance to the appliance hardware and software image.</p> <ul style="list-style-type: none"> • ARRMS operating environment functions completely independently of the main appliance hardware and software environment. The appliance can boot into “maintenance mode” where the administrator has full BIOS-level access to the hardware and software environments, even with the appliance operating system shutdown or the hardware powered off. • System image backup, restore and “Bare-Metal” recovery. Backup any number of system image to local disk partition, removable media or a network target, such images than can be used for a quick restore to “last good known state”. • Factory-default rest and Bare-Metal appliance recovery support
Embedded Web LOM Manager	Remote Lights-Out-Management (LOM) via dedicated iKVM (Keyboard, Video Mouse port access over Web) network Port guarantees uninterrupted Out-Of-Band remote access and manageability for a complete “As if you were sitting in front of it” experience.
Embedded LCD Manager	Headless Appliance Deployment System: Appliance systems include touch-key with graphical LCD hardware and software which allows simple appliance installations without connecting keyboard, mouse and video monitors. This greatly simplifies installs, including remote location installs without local IT support.
Integrated Oneface™ System Manager	Provides rich and robust set of feature including Backup Manager, security manager, update manager, configuration manager, SNMP agents, alert notification system and a component manager for 3rd party add-on integration

nAppliance delivers Integrated Appliance “Turnkey” Solutions:

nAppliance Networks, an ISO 9001:2000 is a provider of mission critical network edge security infrastructure provider. Unlike alternatives that are simply based on general-purpose server hardware, our appliances are designed for highest reliability, optimized for maximum performance, and manufactured to exact quality specifications. Trust nAppliance Net-Gateway Forefront appliance series to deliver reliable and comprehensive solutions.

Performance Specifications

Storage Capacity	: 300GB
Deployment Type (Branch-Office)	: Large Size
Recommended Corporate PCs	: 4,000
Recommended Corporate Web Users	: 20,000
Firewall Throughput (Mbps)	: 2,600
HTTP Throughput (Mbps)	: 240
VPN Throughput (Mbps)	: 200

Hardware Specifications

Processor	Dual Processor, Eight Core Xeon
Memory	16 GB
Network Interfaces (RJ45)	8x GbE LAN
System Management Interface (RJ45)	1x iKVM Lights-Out (IPMI) Remote Access
Storage – Data (Redundant)	SAS Disk, Mirroring (RAID-1), Hot swap
Storage - Recovery OS (ARRMS)	2 GB, USB Flash DOM
SSL HW Accelerator	Cavium CN 1600 Series
LCD w/Keypad Display	Graphical w/ 6-Keypad
System IO Ports (VGA/USB/Serial)	1 / 2 / 1
AC Power Supply	<ul style="list-style-type: none"> • Dual Hotswap Redundant, 650 Watts • 100 to 240 VAC Auto • 47 to 63 Hz, 3A
Physical Dimensions	<ul style="list-style-type: none"> • Chassis: 19”, 4-post rack-mountable • Height: 1.5” (1U), 1 rack unit; • Width: 17.5”; Depth: 27” • Weight: 30 lbs.
Storage Temperature	-40°F to 122°F (-40°C to 50°C) 5% to 95% relative humidity, non-condensing
Operating Temperature	35°F to 95°F (1.7°C to 35°C) 5% to 95% relative humidity, non-condensing
Agency Certifications	Safety: UL, FCC, CE, TUV, CB Environmental: WEEE and RoHS
Support and Services	Standard warranty includes 30-day software support with one-year hardware support; upgradable